Approved For Release: CIA-RDP62S00346A000100030019-4

## BEST COPY

AVAILABLE

#### PRICEBOOK DATA FOR MINING MACHINERY

Machine and Model	DESCRIPTION	Price, rubles
Coal combine, Corniak-1	Output, 30-90 tons/hr. Depth of cut, 1.65- 1.8 meters. Combine electric motor: model MAD-191/11MG, 1465 RPM, hourly power 65 hr, 380 volts. Loader electric motor:MA-191/35G, 1470 RPM, hourly power 35 hr, 380 volts. Weight of combine 8750.5 kg. Price includes electric motors, sprinkler (crositel'neis) pump apparatus, spare parts and tools. Combine weight includes electric motors, spare parts and tools. Spr. tsen, III, 5-6.	90,000
Ortter, 1967-2	Height of sutting notch 140 mm. Length of bar, 2 meters. Cutting speed: working, 2.12 and suxiliary 1.07 met/sec. Electric motor: MA-191/10, 1450 RPM, 47 hw hourly power, 380 volts. Width, 750 mm. Height (excluding parts of sprinkler assembly and local illumination) 375 mm. Length in operating position, 3136 mm. Weight, 3483.5 kg. Price includes electric motor but not magneto starter. Machine can be supplied with bars of length 1.6, 1.8, 2.2 and 2.4 meters and price varies accordingly. Weight of machine indicated for 2-meter bar and including spare parts and tools Spr. tsen, III-6.	34,640
Cutter, CTK-35M	Height of cutting notch, 120 mm. Depth of cut, 2 meters. Cutting speed, 1.82 met/sec. Electric motor: MAD-191/35, 1876/RPM, 35 km hourly power, 380 volts. Dimensions: 2705 x 685 x 310 mm. Weight, with 2-meter ber, 2776.9 kg. Price includes electric motor and spare parts. Cutter can be supplied with bars of length 1.6 and 2.2 meters with corresponding change in price. Spr. teen, III-6.	<b>29,660</b>
Coal shaft linking combine, ME-2M		120,700

#### ABOOK DATA FOR KINING MACHINERY - 2

<b>600e)</b> .	•	DESCRIPT	700			rice,
Conder, 1786-114	front, 2.2 RTSV 110/7 Length vit	meters. 1 550, 670 M h dipper re	pper, 0.2m <sup>3</sup> . No electric: N, 10.5 hr, leased, 2480 osition, 160	motors: 380 volts.		<b>\$</b> ,350
	transport ; railhead; dipper reli electric m	position, l with dipper cased, 1518 otors, 5000	A00 mm. Hei raised, 807 mm. Weight kg. Price Spr. teen,	ght from 0 mm; with with does not	ći i	
ceder, 16-5	Output, 20 htpper, 0. 650-800 hm released,	m <sup>3</sup> /hr. Lo 17 m <sup>3</sup> . Pos N, 10.5 MP. 2270 mm; vi	eding front, weatle motor length wit th dipper re	2000 mm. TR-10, h dipper		15,000
¥ .	without for railbead with dipper relationships	otboard, 10 ith dipper cased, 1500	ootboard, 13 50 mm. Hrig raised,2200 mm. Gauge kg. <u>for.</u> t	ht from my with - 580 and		4
		Work per	tees, III-9)	/	<u>/</u>	
5700	Nodel.	stroke, kg.met.	minute	r Air cols.	re.	Price
normatic, cutting	(MSP-5 (M-1A	3.5 2.5	950 1400	1	10.6	2112
	2014-17A	2.5	1700 1700	2	18.8 18.8	1198 388 497
omml, bering , with lateral flushis	16 1604-18	2.5		- 10 h		677
, with lateral flushis smual, boring	1604-33 1604-33 004-506L 174-508	4.5	1700 1700 1600-1900	2.4 2.4 2.1-2.6	30 30 30.5	617 537. 750
ernal, bering ,with lateral flushis ernal, boring ore drilling, with presentic motor	1616-31 CB-506L	8	1700	12.4	30 30	617 537, 750 2783
, with lateral flushis smual, boring ore drilling, with	MIN-31 CM-506L FM-508 Kind-4	8	1700 1700 1600-1900 1800	12.4	30 30.5 75.5	937 537, 730 2783

### Approved For Release: CIA-RDP62S00346A000100030019-4

#### PRICEBOOK DATA FOR HIRING MACHINERY - 3

Machine and Model	TESCRIPTION	Price, rubles
Electric drill,	Hand drill. Half-output electric motor 0.9 km, 127 volts. Dimensions, 325 x 316 x 224 mm. Wright without cable and plug, 14.6 kg. Price includes plug, detechable gears and spare parts. One starter for every two drills supplied at extra charge. Bor. teen, III-9.	390
Electric drill, ER-5	Hand drill. Helf-hour power 1 hr, 127 volts. Dimensions, 370 x 316 x 224 mm. Weight with-out cable and plug, 17.7 kg. Price inclusions name as ER-4. Apr. team, III-10.	400
Electric crill, EEP-5	With forced feed. Half-hour power 1 hr, 127 volts. Dimensions, 400 x 316 x 250 mm. Weight without cable and plug, 21.5 kg. Price inclusions same as HR-4. Spr. term, 111-10.	
Electric drill, EEE-2A (EEE-2M)	Core type. Ricetric motor: 2950 RPM, hour power 2.7 kg, 220 x 360 volts. Dimensions: 1490 x 382 x 360 mm. Weight without core, bit (bur) and cable, 120 kg. Weight of core, 35 kg. Price includes spare parts, detechable geared wheels and set of tools. The next of the core alone is 135 rubles. Spr. teen, III-10.	1,755
Hand drill, 679-11	Presentic. 2 Mr. Air consumption 2 m <sup>3</sup> /min. Air presence, 5 atm. Dimensions, 370 x 345/x 265 mm. Weight, 12 kg. <u>Spr. teen</u> , III-9.	<b>93</b> 8

(continued)

Approved For Release: CIA-RDP62S00346A000100030019-4

1.00   1.00			% %	176	<b>8</b>	£.35	129/	•	3/12	
	128	1700		1.10	1.93	32.5	8		1887.20	LINE
			·. ·	V	SERVIC CRETER					
	3790		8	1.68	17-17	8.98	9.6	8.8		
	8		8	8	1.77	7.40	-4	3.5		
	138		8	8	1.23	7.79	1.6	10.01		į
	651		8	1.19	1.8	2.12	1.5	0.73	?3	þ
						MAC SON	H			ved F
	8		1900	1.44	1.15	3.91	8.8	8		"
	g		8	1.23	1.39	9.40	8	Tu-Li	\$	ì
	8025		8	1.22	1.39	4.5	8	3.12	9	64
	Se		1967	1.09	1.8	9.60	à	8	? -	,
	8		ş	1.07	1.9	N. 08	2.00	OT.Z		}
	8		900	1.35	1.3	2.77	2.00	2.20	7	7-4
1.05 2.05 1.25 0.07 900 1.24 1.25 1.25 0.07 900 1.24 1.25 1.25 0.07 900 1.24 1.25 1.25 1.25 1.25 1.25 1.24 1.25 1.25 1.25 1.25 1.25 1.25 1.25 1.25				* 40			,		-	A-RD
1.55 2.05 1.55 0.57 500 1155 1.55 0.56 0.50 0.55 0.55 0.55 0.55 0.55 0	176		83	97	<b>11</b>	3.20	2.60	2.36	P688-210	6
	8		88			8	3	3	209	2
1.70 (	3	Ĩ	88	9.97	Į.	, , ,	3 8	7 ·		8
TIRE 1. FINGLES, STEALURE STREET, STRAINER DOTTON  0.70 0.80 1.50 0.90 0.93 750 750 750	238		988	1.34	, i.	N 8	S.S.	N N	20	
THE A. FINGLES, STEALURE SLIME, STEALURE NOTICE	73		750	0.93	0.90	1.50	0.88	9.70	Ö	25-
Total (word) (metage) (metage) (metage) (metage) (metage) (metage)					SEATORIES.		•			0010
	3			(metern)	(motor)	(autore)	(1000)	(2)	2	8
	ľ	Į.			A LA	12		Į		
				No.	WAR.					
•		: -								
									4.	

(				1602	Locator fixe (2)	(2)	·	Ŷ	(क) स्पृष्टिका	
19-4		STATION THE CONTINUES	٠							••
300	Tracki					# E				
boo	force	Speed	!	Electric motors	3	and a		Beight,	Coupling	
0	(33)	121/12r	5	A	volta	paragent of the second	PACE.	rail to	and Cart	Frice,
	occupative							des que	a. tons	rubles
	268 <del>02</del> /	12 is	N	8	X S			/	1	
\$003	4 700			×	No.	1900	1290	1550	W.0	62,000
P62	1700	11.0	N	11.2	No.	1280	10h0;13hoc/	1500	ο.οτ	27,000
-R	1330	11.0	N	41.2	350	1280	970112705/	1500	7.0	3
ci.	200-1	3.6;4.9m.d/	1	2.15;2.804	25	2015	AKOB/	10000		2000
se:	K71	5 7	•				6)60	13000	2.0	otf'21
elea	-17	<b>16.</b> )	<b>P</b>	<b>11.</b>	•	2755	OTG	1450	1.3	14,500
7	Ipcomotives									
For	480	8.3	1	1	ı	2712	80°P	reme/	, ,	
	e Locomotives	3						1,000	0.6	20,300
A PROPERTY OF THE PROPERTY OF	0£TT	6.5	N	<u>v</u>	<b>š</b>	`				
ر	200				!		(20Cortocor	000	8.0	28,500
5-5	2005/	3.614.94	۲	2.15;2.804/	<b>4</b> 5	\$510g	900è/	/qotet	2.0	15.0% 15.0%
John Indicat	Indicated for hourly open man; second figure for an Including folded trolley.	in a serior	bothern	to indication 900 sm. d/couplings.	given b	bor measured. figure, full	rie ja	18	gauge of 550, 575 or chemed field.	275 00
Sime	br avor hnix	ix tour	Ħ	<u> </u>			5)			

CRITICAL

# ELECTRIC MINE LOCOMOTIVES: Price inclusions

Models 14-III, TX-lu: Cost of electric equipment and spare parts included.

Models 10 MB, 7 MR:

Model RSh-2:

Cost of electric equipment, spare parts wor instruments included. Cost of electric equipment and instruments included.

Irolley: Cost of electric equipment and spare parts included.

Model AK-2u:

Nodel SARP or 8 ARPk: Cost of electric equipment, 2 battery cause, one charging table, not included. spare parts, instruments included; cost of alkaline accumulator batteries

cost of accumulator battery not included. Cost of electric equipment, 2 charging tables, and spare parts included;

Approved For Release: CIA-RDP62S00346A000100030019-4